HEIDELBERGCEMENT



HEIDELBERGCEMENT INDIA LTD, AMMASANDRA TEST REPORT FOR MYCEM

REF.: HCIL/QA/2017/14 DATE: 10.05.2017 HCIL(AMS)-QCD-F026

WEEK NO.: 14 02-04-2017 to 08-04-2017

CHARACTERISTIC	RESULTS OBTAINED	REQUIREMENT OF IS455:2015
(A) CHEMICAL COMPOSITION		
(i) Magnesia (MgO), % by mass	8.79	10.0 Maximum
(ii) Insoluble Residue, % by mass	1.50	4.0 Maximum
(iii) Sulphuric Anhydride (SO ₃) % by mass	2.25	3.5 Maximum
(iv) Sulphide Sulphur (S)	0.30	1.5 Maximum
(v) Loss on Ignition % by mass	2.06	5.0 Maximum
(vi) Total Chloride (Cl), % by mass	0.03	0.10 Maximum
(B) PHYSICAL TESTING		
1. Fineness of Cement		
Sp.Surface blaine (m²/Kg)	332	225 m²/kg minimum
2. Soundness		
Le-Chatelier Expansion (mm)	1.0	10 mm Maximum
Autoclave Expansion (%)	0.16	0.8 % Maximum
3. Setting Time		
Initial (in Minutes)	95	Not less than 30 minutes
Final (in Minutes)	200	Not more than 600 minutes
4. Compressive Strength (MPa)		
(a) At 72 ± 1 Hrs.	23.8	16 MPa Minimum
(b) At 168 ± 2 Hrs.	36.8	22 MPa Minimum
(c) At 672 ± 4 Hrs.	52.4	33 MPa Minimum

Remarks:

- 1. Physical Lab Temperature during testing 27 ± 2° C
- 2. Portland Slag Cement conforms to the requirement of IS 455:2015 in all respects.

Mgr (QC)